



PDA-240

The PDA-240 supports manual, auto and one button functions. It ensures reliable transmission for applications which can be DSNG, disaster relief, emergency communications, networks, etc..

The PDA-240 Drive-Away Antenna's precision, and provides remarkably low sidelobes and excellent cross-polar performance. It has a three axes positioner which provides full antenna rotation and is entirely backlash-free in elevation, azimuth and polarization axes.

Light-weight and highly durable structure and aerodynamic design allows interrupted satellite communication anywhere.

COMPATIBILITY

- MIL-STD-810G Compliant
- MIL-STD-1472 Compliant
- MIL-STD-188-164A Compliant
- ITU-RS-580 Compliant
- ITU-RS-465-6 Compliant
- EUTELSAT Compliant

Key Features

- Ku, Ka, C Band options are available
- Antenna pod is designed to accommodate 2 x 400W outdoor HPAs / SSPAs
- Carbon-Fiber composite reflector supported with light weight mount
- Entirely zero-backlash mechanical drive system
- Easy vehicle integration
- Optional beacon tracking
- Optional de-ice
- Manual drive tool kit for emergency situations
- High gain, low side-lobe, high accuracy and very good cross polar rejection (> 35 db)
- Optional hand-held control unit



GENERAL SPECIFICATIONS

Reflector Diameter	2.4m
Reflector Type	Gregorian Offset
Operation On-Air Time	~3 Minutes
Antenna Concept	Gregorian dual offset antenna with 2.4m elliptical carbon-fiber main reflector, folding feed-arm, fixed sub-reflector

RF CHARACTERISTIC

Frequency (GHz)	Tx	13.75~14.50 GHz
	Rx	10.7~12.75 GHz
Antenna Gain (Mid Band)	Tx	48.8+20lg(f/14.25) dBi
	Rx	47.7+20lg(f/12.50) dBi
EIRP		64.8dBW with 40W BUC 68.8dBW with 100W BUC
CPI (On Axis, linear)		35dB
Polarization		Linear
Satellite Operator Compliancy		Compliant with most of satellite operator requirements
VSWR		1.3

MECHANICAL SPECIFICATIONS

	Azimuth	Elevation	Polarization
Drive Rates	0.1° /S ~3° /S	0.1° /S ~3° /S	0.1° /S ~6° /S
Antenna Travels	± 200°	10°~90°	± 90°
Manual Override Mechanism	Manual override for elevation and azimuth drive system		

ENVIRONMENTAL SPECIFICATIONS

Temperature	Operational	-20°C~+55°C
	Survival	-30°C~+70°C
Wind Speed	Operational	72km/h
	Survival	90km/h
Humidity (Relative)		0-95%

Compliances / Certificates



Would you like to get more information?

P : +90 216 540 72 57

M : sales@pals.com.tr

W : www.pals.com.tr

